

WM ME

SIMPLE AND ROBUST
LOADING RAMP.
SUITABLE FOR HEAVY
LOADS, CAPACITY FROM
600 KG TO 1800 KG

LOAD CAPACITY: UP TO 1800 KG



LOAD CAPACITY

600 / 1000 / 1500 /
1800 kg



CUSTOMISED DIMENSIONS

Width from
60 to 137.5 cm
Length from
195 to 325 cm



HANDLING

Horizontal
deployment



COLOUR


Green



Anti-slip rice-pattern
aluminium platform



Wheel for assisted
deployment



Self-positioning
adjustable feet



Mobile contact flap to connect
to the floor of the van






DEPLOYMENT AND CLOSING


The ME ramp is popular for customers needing to load heavy equipment. Deployment of the ramp is simple and quick, thanks to its spring-assisted, fixed vertical, two-section opening. A double-spring version can be supplied on request for larger versions.

OPTIONAL EXTRAS



LEFT HAND SIDE WHEEL KIT

Designed to facilitate ramp deployment, closing and handling. Right hand as standard, or available on left-hand side as an option.



FOLDING SAFETY EDGES

Aluminium safety edges to enhance safety in certain operating conditions.



SUPPLEMENTARY 3RD PIECE KIT

Reduces the ramp angle and results in three folding ramp sections. Ideal for use with small vehicles. Available with capacities up to 1,000 kg, max. width of 100 cm and fixed length of 80 cm.



REMOVABLE EXTENSION KIT

Third removable piece equipped with wheels, to be added to the ramp when necessary. Available for capacities up to 1500 kg, with maximum width of 100 cm.

APPLICATION SECTORS



GARDENING
LAWN
TRACTORS



BUILDING
CONSTRUCTION



QUAD BIKES



CLEANING
MACHINES



PALLET
TRUCKS



PALLETS

EXAMPLE MODELS	A (mm)	L (mm)	L2 (mm)	H (mm)	P (mm)	P1 (mm)	P2 (mm)	Capac. (Kg)	Weight* (Kg)
ME 90	2200	1165	900	1215	95	250	8	600	79
ME 95	2500	1215	950	1365	95	250	8	600	86
ME 100	3000	1265	1000	1615	95	250	8	1000	104
ME 100	3250	1265	1000	1740	95	250	8	1500	122
ME 105	2700	1315	1050	1515	95	250	8	600	94
ME 110	3000	1365	1100	1615	95	250	8	1500	129
ME 110	2500	1365	1100	1365	95	250	8	1000	104
ME 120	2700	1465	1200	1465	95	250	8	1000	115
ME 120	3250	1465	1200	1740	95	250	8	1500	146
ME 125	2800	1515	1250	1515	95	250	8	1000	126
ME 125	3000	1515	1250	1615	95	250	8	1500	143
ME 130	3000	1565	1300	1615	95	250	8	1000	137
ME 130	3250	1565	1300	1740	95	250	8	1500	157
ME 135	3200	1615	1350	1715	95	250	8	1500	158
ME 135	3250	1615	1350	1740	95	250	8	1800	169

* The specified weight does not include the installation kit, which depends on the van. (min. 2 kg - max. 7 kg)

