



WM PC-R

LOADING RAMP WITH ANTI-SLIP MESH PLATFORM, SUITABLE FOR LOADING EQUIPMENT WITH LARGE TYRED WHEELS

LOAD CAPACITY: UP TO 500 KG



Anti-slip mesh platform




Wheel for assisted deployment



Self-positioning adjustable feet



Mobile contact flap to connect to the floor of the van



DEPLOYMENT AND CLOSING

The PC-R and ME-R offer excellent grip for loading goods with large, tyred wheels. The galvanised, expanded metal surface is extremely durable and allows for easy cleaning. Both have the patented, spring-assisted vertical opening for ease of use, with the horizontal swivel offered on the PC-R.

OPTIONAL EXTRAS



FOLDING SAFETY EDGES

Aluminium safety edges to enhance safety in certain operating conditions.




SPECIAL FEET

For loading machines with very low ground clearance, special feet can be supplied to create two different ramp slopes for easier ascent. The specified weight does not include the installation kit, which depends on the van. (min. 2kg - max. 7 kg)



SUPPLEMENTARY 3RD PIECE KIT

Reduces the ramp angle and results in three folding ramp sections. Ideal for use with small vehicles. Available with capacities up to 1,000 kg, max. width of 100 cm and fixed length of 80 cm.



LEFT HAND SIDE WHEEL KIT

Designed to assist the ramp deployment further on to hard ground.

APPLICATION SECTORS



GARDENING
LAWN
TRACTORS



MOTORBIKES
BICYCLES



QUAD BIKES



LOAD CAPACITY
500 kg



CUSTOMISED
DIMENSIONS
Width from
60 to 137.5 cm
Length from
195 to 325 cm



HANDLING
horizontal deployment



ME-R COLOUR
Green

EXAMPLE MODELS	A (mm)	L (mm)	L2 (mm)	H (mm)	P (mm)	P1 (mm)	P2 (mm)	Capac. (Kg)	Weight* (Kg)
PC-R 90	2200	1165	900	1215	95	250	8	500	80
PC-R 95	2500	1215	950	1365	95	250	8	500	87
PC-R 100	3000	1265	1000	1615	95	250	8	500	105
PC-R 100	3250	1265	1000	1740	95	250	8	500	111
PC-R 105	2700	1315	1050	1515	95	250	8	500	95
PC-R 110	3000	1365	1100	1615	95	250	8	500	120
PC-R 110	2500	1365	1100	1365	95	250	8	500	105
PC-R 120	2700	1465	1200	1465	95	250	8	500	116
PC-R 120	3250	1465	1200	1740	95	250	8	500	135
PC-R 125	2800	1515	1250	1515	95	250	8	500	115
PC-R 125	3000	1515	1250	1615	95	250	8	500	134
PC-R 130	3000	1565	1300	1615	95	250	8	500	138
PC-R 130	3250	1565	1300	1740	95	250	8	500	150
PC-R 135	3200	1615	1350	1715	95	250	8	500	151
PC-R 135	3250	1615	1350	1740	95	250	8	500	152

* The specified weight does not include the installation kit, which depends on the van. (min. 2 kg - max. 7 kg)

